

433MHz 1204 Chip Antenna: AAN1204H1R433M

Application:

ISM band, Telemeter, Telemetry, keyless entry system...

Features

SMD, high reliability, ultra Impact, Omni-directional...



Part number

AAN 1204 H1 R 433M
 (1) (2) (3) (4) (5)


| | |
|------------------|---------------|
| (1) Product Type | Chip Antenna |
| (2) Size Code | 12x0.4mm |
| (3) Type Code | H1 |
| (4) Packing | Tape and reel |
| (5) Frequency | 433MHz |

Electrical Specification

| | |
|---------------------------|------------------|
| Centre Frequency | 433 MHz |
| Impedance | 50 Ohm |
| Return loss | 6.5 dB (Min.) |
| Bandwidth | 28M Hz(Typ.) |
| Polarization | Linear |
| Azimuth Beamwidth | Omni-directional |
| Operation Temperature(°C) | -40 ~85°C |

The specification is defined on EVB.

Dimension and Terminal Configuration




| Dimension (mm) | |
|----------------|------------|
| L | 12.0+-0.5 |
| W | 4.0+-0.5 |
| T | 1.5+-0.3 |
| A | 0.85+-0.35 |

| No. | Terminal Name |
|-----|---------------|
| 1 | Feeding |
| 2 | Soldering |

433MHz 1204 Chip Antenna: AAN1204H1R433M

Evaluation Board Reference


PCB Dimension & Antenna Layout Reference





Electrical Characteristics

Return Loss & Radiation

Return Loss





| Frequency (MHz) | S11 (dB) |
|-----------------|----------|
| 433 | -26.4 |



Max gain= -3.31dBi, at (120, 150)
MEG (mean effective gain)= -7.29dBi
Directivity(dB)= 2.82
Efficiency= -6.13dB, 24.38%

Taping Specifications



| Reel | | Taping Blister Tape | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------------------------------------------------------------------|---------------|---------------------------|---|--------------|---------------------------|---|------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------|-----------|---------------|----|------------|-----------------------------------|----|-------------|----------------------------------|---|--------------|-----------------------------------------|----|-------------|---------------------------|----|-------------|----------------------------------|----|-------------|------------|---|--------------|--------------------------------|----|-------------|---------------------------------|----|-------------|--------------------------------|----|------------|-------------------|---|------------|--|
|  | |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Checking note</th> <th>Index</th> <th>Spec (mm)</th> </tr> </thead> <tbody> <tr> <td>Internal diameter of reel</td> <td>A</td> <td>60.20 ± 0.50</td> </tr> <tr> <td>External diameter of reel</td> <td>B</td> <td>180 ± 1.00</td> </tr> </tbody> </table> | Checking note | Index | Spec (mm) | Internal diameter of reel | A | 60.20 ± 0.50 | External diameter of reel | B | 180 ± 1.00 | | <table border="1"> <thead> <tr> <th>Checking note</th> <th>Index</th> <th>Spec (mm)</th> </tr> </thead> <tbody> <tr> <td>Sprocket hole</td> <td>D0</td> <td>1.50 +0.25</td> </tr> <tr> <td>Distance sprocket hole to outside</td> <td>E1</td> <td>1.75 ± 0.10</td> </tr> <tr> <td>Distance sprocket hole to pocket</td> <td>F</td> <td>11.50 ± 0.10</td> </tr> <tr> <td>Distance sprocket hole to sprocket hole</td> <td>P0</td> <td>4.00 ± 0.10</td> </tr> <tr> <td>Distance pocket to pocket</td> <td>P1</td> <td>8.00 ± 0.10</td> </tr> <tr> <td>Distance sprocket hole to pocket</td> <td>P2</td> <td>2.00 ± 0.10</td> </tr> <tr> <td>Tape width</td> <td>W</td> <td>24.00 ± 0.30</td> </tr> <tr> <td>Pocket width nominal clearance</td> <td>A0</td> <td>4.35 ± 0.10</td> </tr> <tr> <td>Pocket length nominal clearance</td> <td>B0</td> <td>12.45± 0.10</td> </tr> <tr> <td>Pocket depth minimum clearance</td> <td>K0</td> <td>1.85± 0.10</td> </tr> <tr> <td>Thickness of tape</td> <td>T</td> <td>0.3 ± 0.10</td> </tr> </tbody> </table> | Checking note | Index | Spec (mm) | Sprocket hole | D0 | 1.50 +0.25 | Distance sprocket hole to outside | E1 | 1.75 ± 0.10 | Distance sprocket hole to pocket | F | 11.50 ± 0.10 | Distance sprocket hole to sprocket hole | P0 | 4.00 ± 0.10 | Distance pocket to pocket | P1 | 8.00 ± 0.10 | Distance sprocket hole to pocket | P2 | 2.00 ± 0.10 | Tape width | W | 24.00 ± 0.30 | Pocket width nominal clearance | A0 | 4.35 ± 0.10 | Pocket length nominal clearance | B0 | 12.45± 0.10 | Pocket depth minimum clearance | K0 | 1.85± 0.10 | Thickness of tape | T | 0.3 ± 0.10 | |
| Checking note | Index | Spec (mm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Internal diameter of reel | A | 60.20 ± 0.50 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| External diameter of reel | B | 180 ± 1.00 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Checking note | Index | Spec (mm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Sprocket hole | D0 | 1.50 +0.25 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Distance sprocket hole to outside | E1 | 1.75 ± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Distance sprocket hole to pocket | F | 11.50 ± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Distance sprocket hole to sprocket hole | P0 | 4.00 ± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Distance pocket to pocket | P1 | 8.00 ± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Distance sprocket hole to pocket | P2 | 2.00 ± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Tape width | W | 24.00 ± 0.30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pocket width nominal clearance | A0 | 4.35 ± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pocket length nominal clearance | B0 | 12.45± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pocket depth minimum clearance | K0 | 1.85± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Thickness of tape | T | 0.3 ± 0.10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <tbody> <tr> <td>Quantity/per reel</td> <td>1000 pcs</td> </tr> <tr> <td>Tape material</td> <td>Plastic (embossed)</td> </tr> </tbody> </table> | Quantity/per reel | 1000 pcs | Tape material | Plastic (embossed) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Quantity/per reel | 1000 pcs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Tape material | Plastic (embossed) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

433MHz 1204 Chip Antenna: AAN1204H1R433M

Reliability Table

| Test Item | Procedure | Requirements Ceramic Type | Remark (Reference) |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|---------------------------|
| Electrical Characterization | | Fulfill the electrical specification | User Spec. |
| Thermal Shock | 1. Preconditioning: $50 \pm 10^{\circ}\text{C}$ / 1 hr , then keep for 24 ± 1 hrs at room temp. 2. Initial measure: Spec: refer Initial spec. 3. Rapid change of temperature test: -30°C to $+85^{\circ}\text{C}$; 100 cycles; 15 minutes at Lower category temperature; 15 minutes at Upper category temperature. | No Visible Damage. Fulfill the electrical specification. | MIL-STD-202 107 |
| Temperature Cycling | 1. Initial measure: Spec: refer Initial spec. 2. 100 Cycles (-30°C to $+85^{\circ}\text{C}$), Soak Mode=1 (2 Cycle/hours). 3. Measurement at 24 ± 2 Hours after test condition. | No Visible Damage. Fulfill the electrical specification. | JESD22 JA104 |
| High Temperature Exposure | 1. Initial measure: Spec: refer Initial spec. 2. Unpowered; 500hours @ $T=+85^{\circ}\text{C}$. 3. Measurement at 24 ± 2 hours after test. | No Visible Damage. Fulfill the electrical specification. | MIL-STD-202 108 |
| Low Temperature Storage | 1. Initial measure: Spec: refer Initial spec. 2. Unpowered: 500hours @ $T=-30^{\circ}\text{C}$. 3. Measurement at 24 ± 2 hours after test. | No Visible Damage. Fulfill the electrical specification. | MIL-STD-202 108 |
| Solderability (SMD Bottom Side) | Dipping method: a. Temperature: $235 \pm 5^{\circ}\text{C}$ b. Dipping time: $3 \pm 0.5\text{s}$ | The solder should cover over 95% of the critical area of bottom side. | IEC 60384-21/22 4.10 |
| Soldering Heat Resistance (RSH) | Preheating temperature: $150 \pm 10^{\circ}\text{C}$. Preheating time: 1~2 min. Solder temperature: $260 \pm 5^{\circ}\text{C}$. Dipping time: $5 \pm 0.5\text{s}$ | No Visible Damage. | IEC 60384-21/22 4.10 |
| Vibration | 5g's for 20 min., 12 cycles each of 3 orientations Note: Use 8"X5" PCB .031" thick 7 secure points on, one long side and 2 secure points at corners of opposite sides. Parts mounted within 2" from any secure point. Test from 10-2000 Hz. | No Visible Damage. | MIL-STD-202 Method 204 |
| Mechanical Shock | Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test specimen (18 shocks) Peak value: 1,500g's Duration: 0.5ms Velocity change: 15.4 ft/s Waveform: Half-sine | No Visible Damage. | MIL-STD-202 Method 213 |
| Humidity Bias | 1. Humidity: 85% R.H., Temperature: $85 \pm 2^{\circ}\text{C}$. 2. Time: 500 ± 24 hours. 3. Measurement at 24 ± 2 hrs after test condition. | No Visible Damage. Fulfill the electrical specification. | MIL-STD-202 Method 106 |

433MHz 1204 Chip Antenna: AAN1204H1R433M

| | | | |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| <p>Board Flex (SMD)</p> | <p>1. Mounting method: IR-Reflow. PCB Size (L:100 × W:40 × T:1.6mm)</p> <p>2. Apply the load in direction of the arrow until bending reaches 2 mm.</p>  | <p>No Visible Damage.</p> | <p>AEC-Q200 005</p> |
| <p>Adhesion</p> | <p>Force of 1.8Kg for 60 seconds.</p>  | <p>No Visible Damage Magnification of 20X or greater may be employed for inspection of the mechanical integrity of the device body terminals and body/terminal junction.</p> | <p>AEC-Q200 006</p> |
| <p>Physical Dimension</p> | <p>Any applicable method using x10 magnification, micrometers, calipers, gauges, contour projectors, or other measuring equipment, capable of determining the actual specimen dimensions.</p> | <p>In accordance with specification.</p> | <p>JESD22 JB100</p> |

Revision History

| Revision | Date | Content |
|----------|-----------|-----------|
| 1 | 2015/7/20 | New issue |